




# FLAMMABLE Solids Cabinets Class 4

Trafalgar Safety is a proudly Australian business which has been creating quality specialty building products and solutions since 1945.

AUSTRALIAN MAD



Removable feet for easy forklift access and mobility

> Right door stays open for easier loading and unloading. 7 locking positions between 20-90 degrees.

#### **Key Features**

- Patented Concealed Stay-Open Sequential Self-Closing Door Mechanism
- 180° opening doors
- Three point self-latching door mechanism
- Fully-adjustable galvanised shelves
- Range of sizes to choose from and custom manufacturing available



Three point self-latching door mechanism

# Storage Solutions

- Flammable Solids Class 4.1
- Spontaneously Combustible -Class 4.2
- Dangerous When Wet Class 4.3





## **Key Features**

1	Powder coating inside and out - durable finish
2	Danger alert sign
3	Ventilation ports, measuring 55mm in diameter
4	Fully welded 150mm deep liquid tight sump
5	Rounded corners on door
6	1.1mm thick double skin wall construction, with 40mm air gap between walls to provide thermal insulation
7	Three point self-latching locking system
8	Continous piano hinges ensuring smooth closure of door
9	Full instructions on usage of cabinet included inside
10	Built in ground connecter

### Flammable Solids Range

Proudly made in Australia, in accordance with Australian Standards and comply with AS 1940-2017. Patented concealed 'Stay-Open' double door design makes loading and unloading dangerous chemicals safer and easier.





60L



100L





### Flammable Solids Cabinet Range

Part Number	Capacity	Shelves	External Dimensions (mm)			Internal Dimensions (mm)			Weight
	(L)		Height	Width	Depth	Height	Width	Depth	(kg)
TCFLS30L	30	1	805	520	475	535	425	375	53
TCFLS60L	60	2	1070	520	475	800	425	375	62
TCFLS100L	100	1	810	935	680	560	835	530	100
TCFLS160L	160	2	1295	1115	525	1045	1015	375	138
TCFLS250L	250	3	1830	1115	525	1580	1015	375	187

NOTE: External dimensions for height for all models except 30L and 60L increase by 95mm with removable feet attached.

